

RM Cores (6298280121)



Part Number: 6298280121

98 RM CORE SET

RM (Rectangular Modulus) cores allow better shielding than E type geometries while also providing easier winding accessibility and better power dissipation than a pot core configuration. Fair- Rite \(\sigma \) standard RM cores all have a solid center post and standard height, low profile and alternate materials are available upon request.

 \square RM cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

Weight indicated is per pair or set.

Weight: 22 (g)

	1 -2 (8)		T	1	
Dim	mm	mm tol	nominal inch	inch misc.	
A	27.8	± 0.60	1.094	_	
В	9.3	± 0.15	0.366	_	
C	13.25	± 0.25	0.522	_	$\begin{array}{c} \textbf{Chart Legend} \\ \hline \Sigma I/A : Core Constant, & l_e : Effective Path \\ \hline Length, & A_e : Effective Cross- Sectional Area, & V_e \\ \hline Effective Core Volume \\ \hline A_L : Inductance Factor \\ \hline \end{array}$
D	6.4	± 0.20	0.252		
Е	21.65	± 0.45	0.852		
F	10.65	± 0.20	0.419	_	
G	12.5	min	0.492	min	
J	24.15	± 0.55	0.951		
& 4 =	materia	l grade.		,	Explanation of Part Numbers: Digits 1 & 2 = product class and

Electrical Properties				
$A_L(nH)$	$4300 \pm 25\%$			
Ae(cm ²)	0.898			
$\Sigma l/A(cm^{-1})$	5.3			
l _e (cm)	4.79			
$V_e(cm^3)$	4.306			
$A_{\min}(cm^2)$	0.884			

A_L value is measured at 1 kHz, B < 10 gauss.

888-324-7748

Fair- Rite Products Corp.

One Commercial Row, Wallkill, New York 12589-0288

845-895-2055

Fax: 845-895-2629

ferrites@fair- rite.com

www.fair- rite.com