

ETD Cores (9598545402)



Part Number: 9598545402

98 ETD CORE SET

ETD cores have been designed to make optimum use of a given volume of ferrite material for maximum throughput power, specifically for forward converter transformers. The structure, which includes a round center post, approaches a nearly uniform cross- sectional area throughout the core and provides a winding area that minimizes winding losses. ETD cores are used mainly in switched- mode power supplies and permit off- line designs where IEC and VDE isolation requirements must be met.

 \Box ETD cores can be supplied with the center post gapped to a mechanical dimension or an A₁ value.

Weight indicated is per pair or set.

Weight: 180 (g)

$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	v cigiit	<u>. 100 (</u>	<i>5)</i>			
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	Dim	mm	mm tol	nominal inch	inch misc.	
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	A	54.2	± 1.00	2.134		
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	В	27.1	± 0.30	1.067		
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$		18.9	± 0.40	0.744		
	D	19.5	± 0.30	0.768		
Effective Core Volume : Inductance Factor	Е	40.5	min	1.594	min	, ,
: Inductance Factor	F	18.9	± 0.30	0.744		
Explanation of Part Numbers: Digits 1 & $2 = \text{product class}$ and 3 & $4 = \text{material grade}$.	A _L :	Induc	tance Facto	or _		— Effective Cole volume
	Explan	ation o	of Part Nur	nbers: Digits 1 & 2	= product class a	nd 3 & 4 = material grade.

Electrical Properties					
$A_L(nH)$	5400 ±25%				
Ae(cm ²)	2.65				
$\Sigma l/A(cm^{-1})$	4.7				
l _e (cm)	12.56				
$V_e(cm^3)$	33.3				
$A_{min}(cm^2)$	2.4				

A₁ value is measured at 1 kHz, B < 10 gauss

Fair- Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288

ferrites@fair- rite.com

www.fair- rite.com

888-324-7748 • 845-895-2055 • Fax: 845-895-2629 •